



RHW SERIES DELTA HAND WINCHES

500kg / 1000kg / 2000kg / 3000kg

FEATURES INCLUDE

- Rated for pulling applications
- Large drum capacity
- Two position handle with short arc rachet facility
- Available in galvanized (G), or painted (P) finish
- Ratchet brake
- Light weight, simple to use
- Base mounting
- Free wheel payout facility

OPTIONAL WIRE ROPE LENGTHS

Wire ropes are sold separately
 Lengths supplied to suit requirements
 up to maximum storage stated below

SPECIFICATIONS KNW-0500d/P KNW-1000d/P KNW-2000d/P KNW-5000d/P	SPECIFICATIONS	RHW-0500G/P	RHW-1000G/P	RHW-2000G/P	RHW-3000G/F
--	----------------	-------------	-------------	-------------	-------------

Rated Load 1st Layer	500kg	1000kg	2000kg	3000kg	
Working Load 3rd Layer	340kg	718kg	1455kg	2136kg	
Maximum Rope Storage (with free board)	22m	25m	30m		
Hand Force Required (min.)	12kg		15kg	20kg	
Gear Ratio	4.3:1	12.2:1	22.7:1	29.2:1	
Handle Length	380mm on all models				
Drum Ø	60mm	76mm	90mm	100mm	
Wire Rope Ø recommended	7mm	8mm	9mm	11mm	
Net Weight approx.	14kg	19kg	25kg	44.5kg	

Use the affixes (G) or (P) to specify galvanised or painted finish

NOTES

These winches must not be used for the movement of personnel and 5 wraps of wire rope must be maintained on the drum.

Data shown is approximate and intended as a guide only.

You are strongly advised to carry out a risk assessment before selecting a manual winch for any proposed application.

WARRANTY

Each new winch is guaranteed against defects in workmanship and material defects for a period of twelve months from date of purchase.

Wire ropes are not included under warranty.

REMSA CE





Bushey Hall Winchmaster sales@bhwgroup.co.uk www.bhwgroup.com