



CTE SERIES DELTA CHAIN HOIST

Lug Type

500kg to 15000kg

415v AC 3ph @ 50Hz

FEATURES INCLUDE

- *Low headroom design*
- *High duty cycle, 360 starts / hour*
- *Heavy duty motor*
Insulation class H
- *Increased lifting speeds*
- *Dual speeds available (see list page 2)*
- *Higher horse power*
- *True modular design*
- *Chain bag supplied as standard*
- *Unique DC Brake*
Does not break the kinetic bond between the holding brake and the lifted load
- *Additional manual release on brake*
Incorporated into hoist in case of mains failure
- *Overload protection*
Through advanced external slip clutch
- *Sealed electrical enclosure*
- *4 button, 24v plug-in pendant control*
Supplied as standard, 48v versions also available
- *Wrap Around Frames on trolleys*
With safety lugs and bumpers

OPTIONS

- *Soft Start*
- *Chains are sold separately*
Lengths supplied to suit requirements and fall
- *Chain bags*
There are several sizes available according to chain length required

ALTERNATIVE CHAIN HOISTS AVAILABLE

- *Light Duty - LD Jobber 500kg or 1000kg*
- *Suspension Hook - CTS Series 500kg to 15000kg*
- *Plain Trolley - CTY Series 500kg to 15000kg*
- *Motorised Trolley - CTD Series 500kg to 15000kg*
- *Geared Trolley - CTZ Series 500kg to 15000kg*
- *Double Girder Trolley - CTH Series 500kg to 15000kg*

SPECIFICATIONS

Model	Capacity	Frame	Dual Speed?	Speed m/min	No. falls of chain	Net weight
CTE.151.001	500kg	C 015A		8	1	54kg
CTE.151.003	500kg	C 015A	Yes	8 & 2.7	1	56kg
CTE.30F.001	1000kg	C 015B		4	1	60kg
CTE.30F.003	1000kg	C 015B	Yes	4 & 1.3	1	62kg
CTE.301.001	1000kg	C 030A		8	1	71kg
CTE.301.003	1000kg	C 030A	Yes	8 & 2.7	1	76kg
CTE.451.001	1500kg	C 050A		9.5	1	141kg
CTE.451.003	1500kg	C 050A	Yes	9.5 & 3.2	1	145kg
CTE.302.001	2000kg	C 030A		4	2	80kg
CTE.302.003	2000kg	C 030A	Yes	4 & 1.3	2	85kg
CTE.601.001	2000kg	C 060A		8	1	141kg
CTE.601.003	2000kg	C 060A	Yes	8 & 2.7	1	145kg
CTE.751.001	2500kg	C 075A		7.3	1	161kg
CTE.751.003	2500kg	C 075A	Yes	7.3 & 2.4	1	165kg
CTE.303.001	3000kg	C 030A		2.7	3	99kg
CTE.303.003	3000kg	C 030A	Yes	2.7 & 0.9	3	104kg
CTE.452.001	3000kg	C 050A		4.8	2	169kg
CTE.452.003	3000kg	C 050A	Yes	4.8 & 1.6	2	173kg
CTE.752.001	5000kg	C 075A		3.7	2	231kg
CTE.752.003	5000kg	C 075A	Yes	3.7 & 1.2	2	235kg
CTE.753.001	7500kg	C 075A		2.5	3	291kg
CTE.753.003	7500kg	C 075A	Yes	2.5 & 0.8	3	295kg
CTE.754.001	10000kg	C 075A		3.7	4	485kg
CTE.754.003	10000kg	C 075A	Yes	3.7 & 1.2	4	493kg
CTE.756.001	15000kg	C 075A		2.5	6	545kg
CTE.756.003	15000kg	C 075A	Yes	2.5 & 0.8	6	553kg

NOTES

These hoists must not be used for the movement of personnel.

Data shown is approximate and intended as a guide only.

You are strongly advised to carry out a risk assessment before selecting a manual winch for any proposed application.

WARRANTY

Each new hoist is guaranteed against defects in workmanship and material defects for a period of twelve months from date of purchase.

Chains are not included under warranty.