

WK-100S SPECIFICATIONS

Control module		Indirect control +Wireless Control	
Frequency band		433MHz	
Typical operating range		100 M (328 ft)	
Applicable current		AC 110V 15A / 220V 7.5A / 240V 7.5A	
Function		Go up / Go down / Emergency stop	
Control Unit	Power	Current range	110V OR 220V OR 240V
	Input	Power lead for main power source	2.0 mm x 3C/3P quick connector
	Power	Power lead for winch	2.0 mm x 3C/3P quick connector
	Output	Control lead	2.0 mm x 6C/6P quick connector
	Contactors	Number	3 sets
	Receiver	Power supply	AC 110V / 220V / 240V
		Function	Go up/ Go down / built-in buzzer
	Protection degree		IP67
Transmitter	Power supply		DC3V
	Button		Emergency stop switch, Power on switch
	Power consumption		16mA
	Battery		LR6(AA)1.5V*2
	Protection degree		IP65
Environment	Operating temperature		-25°C ~ + 55°C
	Storage temperature		-40°C ~ + 65°C
	Humidity		90%RH
Complied with RED directive		2014/53/EU	

Standard Accessories

- Control Box
- Base plate
- Wireless remote control

Package

- Net weight: 3.7 kg / 8.2 lb
- Gross weight: 4.5 kg / 9.9 lb
- Box dimension: 286 x 266 x 170 mm
(12.0" x 10.5" x 6.7 ")